IDDEA

TR2340

Linha THIN CLIENT

ITENS		SPECIFICATIONS
Processor		• AMD Gx466 (333MHz)
I/O Peripheral & Comunication		• 10/100 dual speed Ethernet, Twisted Pair (RJ45) • One serial port • Enhanced ps/2 keyboard interface • Enhanced ps/2 mouse interface • Three USB ports • One 16-Bit Stereo 44.1KHz Audio Output • One microphone Input
Option Embedded O.S		• Microsoft Embedded XP • Linux • Microsoft Windows CE 5.0 or later
Special support		• PXE enabled on Bios • Built-in auto. power-on support • External CF card support (CF card accessible)
Option support		• Kensington lock support for security (option) • Wall mount kit support (option)
Display Resolution		• Support 640x480, 800x600, 1024x768, 1280x1024, 1600x1200 with 32 bits color. • Flicker free, max. up to 85 Hz
Memory		• RAM DDR-RAM o 128/256/512 MB • Flash o 32/128/256/512 MB CF card or DOM
Environment	Temperature	• Operating: 5 ºC to 35 ºC (41 ºF to 95 ºF) • Storage: -20 ºC to 60 ºC (-4 ºF to 140 ºF)
	Relative Humidity	• 90% maximum, non-condensing
	Operating Altitude Range	• 0 to 10,000 feet (0 to 3050 meters)
	Power	• External power adapter with full range auto-sensing 100 ~ 240 VAC at 50 Hz ~ 60 Hz. • 2A/12V (24 Watts)
Regulatory Compliance		• UL, C-UL, TUV/GS, FCC Class B, CE mark
Physical Caracteristics	Dimension (WxDxH)	• 194.5 x 151.5 x 40 (mm)
	Weight	• 0.65 Kg

Kensington lock support

External CF card support

Wall mount design & kit

Wall mount design & kit